

# HEAVY HEX NUTS A194 GRADE 8FA (303S)

## ***SUBMITTAL SPECIFICATION***

"ABSTRACT OF ASTM ASTM A194"

"CARBON AND ALLOY STEEL NUTS FOR HIGH-PRESSURE AND HIGH-TEMPERATURE SERVICE"

**GRADE:** AISI TYPE 303 WITH SULFUR, ASTM A194-8FA

### **CHEMICAL REQUIREMENTS (%):**

CARBON, MAX	0.15
MANGANESE, MAX	2.00
PHOSPHOROUS, MAX	0.20
SULFUR, MIN	0.15
SILICON, MAX	1.00
CHROMIUM	17.00 - 19.00
NICKEL	8.00 - 10.00

### **MECHANICAL REQUIREMENTS:**

<u>ALL DIAMETERS</u>	<u>MINIMUM</u>	<u>MAXIMUM</u>
PROOF LOAD	SEE SPEC FOR PROOF LOADS ON INDIVIDUAL SIZES	
HARDNESS (BRINELL)	126	192
HARDNESS (ROCKWELL)	B60	B90

**IDENTIFICATION SYMBOL:** 8FA

### **OTHER:**

ALL NUTS, UNLESS OTHERWISE SPECIFIED IN THE PURCHASE ORDER SHALL BE THREADED IN ACCORDANCE WITH ANSI/ASME B1.1 UNIFIED INCH SCREW THREADS, CLASS 2B (INTERNAL) FIT. NUTS SHALL BE IN ACCORDANCE WITH THE DIMENSIONS OF ANSI/ASME B18.2.2, HEAVY HEX NUTS. UNLESS OTHERWISE SPECIFIED IN THE PURCHASE ORDER, THE HEAVY HEX NUT SERIES SHOULD BE USED.

**Pacific Coast Bolt**

12748 East Florence Ave Santa Fe Springs, CA 90670  
1-800-652-6587 Fax 1-562-944-9360

REV. 02/09